

KM-3040

► print ► copy ► scan ► fax

A3 MONOCHROME MULTIFUNCTIONAL

UPGRADE TO MORE FLEXIBILITY.

As your business needs grow, there's no reason why your devices shouldn't grow too. The KM-3040 can be upgraded from a highly efficient copier to a flexible multifunctional, thanks to additional print and fax options. With long-life components ensuring reliability, it takes care of whatever the future holds.

- Fast, 15 second warm-up time
- Universal, energy-saving design
- Dark-coloured inner paper tray to confirm output at a glance
- Ergonomic paper cassette grip
- Two 500-sheet paper feeders and internal 200-sheet multi-purpose tray
- Long-life components

Product depicted includes optional extras



Large and adjustable control panel with easy-to-use intuitive menus.



200-sheet multi-purpose tray allows additional paper input.



KM-3040

A3 MONOCHROME MULTIFUNCTIONAL

The KM-3040 incorporates extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The KM-3040 provides effective productivity and maximises up-time whilst ensuring a minimum impact on the environment.

GENERAL

Technology: Kyocera Laser, Mono component
Engine speed: Max. 30/15 pages per minute A4/A3
Resolution: 600 x 600 dpi (copy), 1,800 dpi level x 600 dpi (copy, photo mode), 1,200 dpi quality (print)
Time to first copy: 4.7 seconds or less
Warm-up time: 15 seconds or less from power on
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 560 W, Stand-by: 160 W, Power-Saving (ECOpower): 3.2 W
Noise (ISO 7779): Printing/copying: 66.5 dB(A), Stand-by: 47 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): Main unit: 570 x 640 x 767.2 mm
Weight: Main unit: Approx. 75 kg
Certifications: TÜV/GS, CE
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 2 x 500-sheet universal paper feeder, 60-120 g/m², A3-A5R, Folio
200-sheet multi-purpose tray, 45-200 g/m², A3-A6R, Folio, envelopes
Max. input capacity with options: 2,200 sheets
Duplex as standard supports A3-A5, 60-80 g/m²
Output capacity: 250 sheets face-down

COPY FUNCTIONS

Max. original size: A3
Continuous copying: 1-999
Memory capacity: Standard 64 MB (max. 192 MB)
Zoom range: 25-400% in 1% steps (with DP-670: 25-200%)
Pre-set magnification ratios: 5R / 5E
Digital features: Interrupt output job, scan once print many, electronic sort, rotate sort, rotate copy, N-up copy, split copy, cover mode, page numbering, margin shift, border erase
Exposure mode: Auto, manual: 7 or 13 steps
Image adjustments: Text + photo, text, photo

PRINT FUNCTIONS (OPTIONAL)

Processor: PowerPC 750CXr / 400 MHz
Memory: Standard 64 MB (max. 576 MB) + 40 GB HDD (HD-5)
Emulations: PCL6 incl. P.J.L, KPDL 3 (PostScript 3 compatible)
Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, KC-GL, PDF direct print

Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts (PCL6), 136 PostScript KPDL 3 fonts, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Features: eMPS – for quick copy, proof and hold, private print, job storage and job management functionality

Interfaces

Standard interface: USB 2.0 (Hi-Speed), Fast Ethernet
10-Base-T/100Base-TX, CF slot, KUIO-LV option interface slot
Multiple interface connection (MIC): Allows simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: 3 seconds or less (JBIG)
Scanning density: Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superfine: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm (with optional memory), halftone
Max. original size: A3
Compression method: JBIG, MMR, MR, MH
Memory: Standard 4 MB, max. 32 MB
Features: Rotate transmission, confidential, relay and bulletin board transmission

OPTIONS

Printing System (Y), Fax System (P)

Paper handling
DP-670 Document processor: 75 sheets, 45-160 g/m², A3-A5R, Folio (RADF)
PF-670 Paper feeder: 2 x 500 sheets, 60-120 g/m², A3, A4, A4R, A5R, B4, B5, B5R, Letter, Letter-R, Legal, Ledger, Folio, STMT
DF-670 Document finisher: Max. 500 sheets A4 or 250 sheets A3, Folio, 60-105 g/m², one position stapling max. 30 sheets A4 or 20 sheets A3
DF-730 Document finisher + AK-670*: Max. 1,000 sheets A4 or 500 sheets A3/B4, 64-128 g/m², A3-B5, one position stapling max. 30 sheets A4 or 20 sheets A3/B4, 64-128 g/m²
JS-670 Job separator: 100 sheets internal job separator, 45-160 g/m², A3-A5R

*Adapter-Kit AK-670 is required for the use of DF-730 document finisher.

Memory

Copy Memory
DIMM memory: SDRAM DIMM (64, 128 MB), 1 slot empty
Printer Memory
DIMM memory: DDR-SDRAM DIMM (64, 128, 256, 512 MB), 1 slot empty
CompactFlash® card: 1 slot (up to 4 GB) for forms, fonts, logos, macro storage
HD-5 Hard disk: 40 GB, storage of data, formats, fonts etc. + eMPS, booklet printing
Fax Memory
MM-13-32: Image memory (28 MB)

Optional interface for print functions

IB-23 Network card: 10Base-T/100Base-TX
SB-70 Network card: Wireless LAN – IEEE 802.11b
SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic
SB-110 Network card: 10Base-T/100Base-TX

Others

Platen cover (D)
CB-670 Cabinet: Wooden desk with storage capacity
CB-671 Cabinet: Metal desk with storage capacity

CONSUMABLES

TK-675 Toner-kit: Microfine toner for 20,000 pages with 6% coverage



Select your options to suit your needs:



Product depicted includes optional extras

Your Kyocera Business Partner:

KYOCERA MITA Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com
KYOCERA MITA Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA