

AN EASY-TO-USE SOLUTION FOR YOUR LARGE FORMAT DOCUMENT MANAGEMENT.

Compact and quiet, the Kyocera KM-3650w offers a full range of easy-to-use solutions for your large format printing, copying and scanning needs up to A0. Simple day-to-day operation and maintenance make this multi-functional a highly efficient addition to your office.

- Copy/print speed of 3.6 m per minute
- Sharp and detailed output quality
- Face-up original feed ensures that the right copies go in the right way
- High-efficiency mono-component toner for environmentally friendly printing
- Zoom range from 25 % to 400 %, selectable in increments of 0.1 %



The operating panel with angle adjustment is located for easy access, ensures optimal operating comfort and let you avoid reflection from ambient lighting.



With space for up to two rolls, there is no need to constantly refill the paper supply, even if the work load picks up.



KM-3650w

A0 MONOCHROME MULTIFUNCTIONAL

The KM-3650w incorporates extremely durable components that guarantee efficient and reliable operation. The system is designed to meet the demanding requirements of busy office environments. The KM-3650w provides effective productivity and maximises uptime whilst ensuring a minimum impact on the environment.

GENERAL

Technology: LED + indirect, electrostatic method
Engine speed: 4.3 (A1), 2.6 (A0) sheets per minute, 3.6 meters per minute
Resolution: 600 x 600 dpi (print/copy)
Time to first copy: 40 seconds (A1)
Time to first print: 24 seconds (A1)
Warm-up time: 300 seconds or less from power on, 120 seconds or less from low power mode
Power source: AC 220 ~ 240 V, 50 Hz
Power consumption: Copying/Printing: 1000 W or less, Ready mode: 500 W or less, Sleep/off mode: 65 W or less
Noise (ISO 7779/ISO 9296): Copying/Printing: 60 dB(A), Ready mode: 54 dB(A)
Dimensions (W x D x H): Main unit: 1260 x 600 x 1101 mm
Weight: Approx. 210 kg
Certifications: TÜV/GS, CISPR22 Class B
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

Input capacity:
1 Roll + 1 sheet bypass: Max. 2 rolls + 1 sheet bypass
150 m/roll, paper roll width 279 ~ 914 mm, bypass paper width 279 ~ 914 mm, bypass paper length 210 ~ 1,219 mm, 64 to 80 g/m²
Output capacity: 10 sheets

COPY FUNCTIONS

Max. original size: 914 x 12,000 mm
Min. original size: 279 x 210 mm
Copy size: Max. 914 x 12,000 mm, min. 279 x 210 mm
Print size: Max. 914 x 24,000 mm, min. 279 x 210 mm
Continuous copying: 1-99
Memory capacity: Standard 512 MB and 80 GB HDD
Zoom range: 25-400% in 0.1% steps
Preset magnification ratios: 4R / 4E
Digital features: Paper type selection, interrupt copy, automatic drawer change, repeat copy, scan one copy many, application copy, rotation copy, mirror image, sort, group, background removal, date stamp, margin shift, border erase, sharpness

PRINT FUNCTIONS

Processor: Celeron D 2.6 GHz or more
Memory: Standard 512 MB and 80 GB HDD (shared with copy memory)
Emulations: HP-GL / HP-GL2 / HP-RTL
Calcomp 906 / 907
TIFF 6.0 (G3, G4)
CALs (G4), BMP, JPEG
Option: PDF
Printer driver: Windows® printer driver
OS: Windows® 2000, XP
Auto CAD HDI driver: Auto CAD 2000, 2000i, 2002, 2003, 2004, 2005, 2006
Printer utility: For client
OS: Windows® 2000, XP

INTERFACE

Standard interface: 10Base-T/100Base-TX

SCAN FUNCTIONS (OPTIONAL)

Functionality: Scan-to-PC/FTP
Scan speed: 4.2 (A1), 2.6 (A0) sheets per minute in 600 dpi, line mode, 5%
Scan resolution: 600, 400, 300, 200, 100 dpi
Maximum scan size: A0
Interface: 10Base-T/100Base-TX
File types: TIFF (G3, G4), CALs-G4, BMP, PDF, JPEG
Features: Scan to folder, density adjustment (7 steps), continuous scan, background removal, border erase, mirror image, scan + copy

OPTIONS

Roll unit (RU-5), Scan system 1, Bay folders

CONSUMABLES

TK-950 Toner-kit: Toner for 2,400 m with A0 width 5% coverage
Toner for 2,000 m with A0 width 6% coverage



Roll unit (RU-5)

Product depicted includes optional extras

Your Kyocera Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com
Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

 **KYOCERA**